


OUTDOOR-FIT

exercise systems

OUTDOOR FIT EXERCISE SYSTEMS

#4-50 THORNHILL DRIVE
DARTMOUTH, NS B3B 1S1
TOLL FREE: 1 (877) 760-6337
PHONE: (902) 444-3447
FAX: (902) 442-8860
www.outdoor-fit.com



SPECIFICATIONS:

ANCHORING: 4 x CONCRETE ANCHORS WITH RATED "PULL OUT" OR "TENSION" STRENGTH OF 3400LBS OR GREATER. ANCHORS MUST BE SECURED INTO STRUCTURAL CONCRETE.

MATERIAL: 3/16" AND 1/4" HEAVY DUTY STEEL, URETHANE RUBBER WITH A 60 DUROMETER.

FINISHES: ZINC PRIMED AND POLYESTER POWDER COATED WITH UV STABILIZED COLOR PIGMENT


STANDARD COLOR: RAL 5001 GREEN BLUE; CUSTOM COLORS AVAILABLE FOR AN EXTRA CHARGE

HEIGHT: 56" (143 CM); **WEIGHT:** 155 LBS (71 KG)

NUMBER OF SIMULTANEOUS USERS: 2

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 4895-031.



OUTDOOR FIT

FLEX MULTI-STRETCH